

AFTER INSTALLATION

Area use after the installation

After the installation is complete, the area should be left open for air ventilation, or turn on the air conditioner in order to allow the water in the adhesive to evaporate and allow the adhesive to have the highest adhesion strength (about 2-3 days). The air inside the room should not be too hot (not above 45 degree Celsius) because it will affect the installation. Do not move heavy weight items within 1 week. Do not use water to clean the floor as soon as the installation is complete. If there is dirtiness, use a damp mop to wipe and clean the floor. Dragging items that have hardness, heavy weight or sharpness can cause the surface to be permanently scratched. Wheel or paving materials made from low-quality rubber can cause black stains on the floor.

Cleaning

Daily cleaning can be performed by using damp cloth moistened with neutral cleaning solution or soapy water to wipe and clean daily. In case of using automatic floor cleaning machines, use a soft or moderately-hard scrub pad.



Surface coating with DYNOWAX water-based acrylic wax

If it is a new tile installation area, clean the dust or dirty stain first, and then waxing process may be performed by using a mop made of fine fabrics or using an automatic coating machine. In case of requiring multiple coatings, please wait for the previously-coated wax to be completely dry before coating the next layer. If you want additional polish, you can use a high-gloss polishing solution and high-rev buffer to make wax surface more shiny.



Floor improvement and dirtiness cleaning

If the vinyl tile floor is very dirty, it should be cleaned with a low-rev buffer. Use the polishing pad with the highest roughness (black) and use the DYNOKLEEN waxing remover to remove all dirtiness. Then, clean off the leftover of the solution with a small amount of clean water. Use with buffer equipped with moderate roughness polishing pad. Wipe or blow to dry off, and then coat with DYNOWAX as usual.